



# ENERG

енергия · ενεργεια



1008004102

alpha innotec

Paros 4-2



55 °C

35 °C



**43** dB



**41** dB





# ENERGY

1008004102

alpha innotec

Paros 4-2



55 °C

35 °C



**43** dB



**41** dB





# ENERG

енергия · ενεργεια

Y

IJA


IE

IA

1008004102

alpha innotec

Paros 4-2 + Lux 2.1



A<sup>++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

B

C


D

E

F

G

+



+



+



+



package (heat pumps and combination heater with heat pump) - Paros 4-2 + Lux 2.1

Seasonal space heating energy efficiency of heat pump ( $\eta_s$ ) ① 138 %

**Rated heat output of the heat pump ( $P_{rated}$  kW)** 4

Temperature control Class II (Table 1) + ② 2 %

Supplementary boiler  
package with hot water storage tank no  $P_{sup}$  kW (rated heat output of supplementary heater)

$\eta_s$  % ( $\sigma_{\pi}$ )  $(\eta_s \% (sup) - ①) \times (\alpha_{WP}) =$  - ③

( $\alpha_{WE}$ : see Table 3)  $(\alpha_{WE})$

solar contribution  $(A_{Koll} m^2)$   $(\eta_{Koll} \%)$   
 $(V_{Sp} m^3)$   $(standstill\ heat\ loss\ of\ the\ hot\ water\ storage\ tank\ in\ W)$   
 $(\eta_{Sp}: Table\ 2)$

$((294/P_{rated} \times 11) \times (A_{Koll} m^2) + (115/P_{rated} \times 11) \times (V_{Sp} m^3)) \times 0,45 \times ((\eta_{Koll} \%) / 100) \times (\eta_{Sp}) =$  + ④

Seasonal space heating energy efficiency of package ⑤ 140 %

*rounded to the nearest integer*

Seasonal space heating energy efficiency class of package



Seasonal space heating energy efficiency under colder or warmer climate conditions

Seasonal space heating energy efficiency of the heat pump ( $\eta_s$ ) under colder climate conditions 111 %

Seasonal space heating energy efficiency of the heat pump ( $\eta_s$ ) under warmer climate conditions 164 %

colder ⑤ 140 -V 27 = 113 warmer ⑤ 140 +VI 26 = 166

|   |               |                  |     |
|---|---------------|------------------|-----|
| <b>heatpump datasheet:</b>  |               |                  |     |
|   |               |                  |     |
| <b>manufacturer:</b>  | alpha innotec |                  |     |
| <b>model:</b>   | Paros 4-2     |                  |     |
|   |               |                  |     |
| <b>Information concerning energy efficiency class and rated heat output:</b>  |               |                  |     |
|   |               |                  |     |
|   | average / low | average / medium |     |
| energy efficiency class space heater:   | A+++          | A++              | -   |
| rated heat output:  | 5             | 4                | kW  |
| energy efficiency space heater:   | 180           | 138              | %   |
| annual final energy consumption space heater  | 2257          | 2347             | kWh |
|   |               |                  |     |
| sound power level indoors   |               | 43               | dB  |
|   |               |                  |     |
| <b>special precautions concerning assembly, installation or maintenance</b>   |               |                  |     |
| All instructional work in this manual may only be carried out by qualified specialist personnel in compliance with local regulations. |               |                  |     |
|   |               |                  |     |
| <b>additional information</b>   | low           | medium           |     |
| rated heat output colder climate  | 5             | 5                | kW  |
| rated heat output warmer climate  | 4             | 4                | kW  |
| energy efficiency space heater colder climate   | 137           | 111              | %   |
| energy efficiency space heater warmer climate   | 215           | 164              | %   |
| annual energy consumption space heater colder climate   | 3520          | 3899             | kWh |
| annual energy consumption space heater warmer climate   | 947           | 1257             | kWh |
|   |               |                  |     |
| sound power level outdoors  |               | 41               | dB  |

|  |                      |   |
|--|----------------------|---|
| <b>technical data of the temperature controller</b>                  |                      |   |
|  |                      |   |
| <b>manufacturer:</b>   | <b>alpha innotec</b> |   |
| <b>model:</b>  | <b>Lux 2.1</b>       |   |
|  |                      |   |
| controller class   | II                   | - |
| contribution of the controller to the energy efficiency space heater | 2                    | % |

|  |   |              |             |  |                   |              |                   |
|--|---|--------------|-------------|--|-------------------|--------------|-------------------|
| <b>Model</b>   |   |              |             | <b>Paros 4-2</b>   |                   |              |                   |
| Air-to-water heat pump: (yes/no)   |   |              |             | yes  |                   |              |                   |
| Brine-to-water heat pump: (yes/no)   |   |              |             | no   |                   |              |                   |
| Water-to-water heat pump: (yes/no)   |   |              |             | no   |                   |              |                   |
| Low-temperature heat pump: (yes/no)  |   |              |             | no   |                   |              |                   |
| Equipped with supplementary heater: (yes/no)   |   |              |             | yes  |                   |              |                   |
| combination heater with: (yes/no)  |   |              |             | no   |                   |              |                   |
| application: (low/medium)  |   |              |             | medium   |                   |              |                   |
| climate: (colder/average/warmer)   |   |              |             | average  |                   |              |                   |
| <b>Item</b>  | <b>Symbol</b>   | <b>Value</b> | <b>Unit</b> | <b>Item</b>  | <b>Symbol</b>     | <b>Value</b> | <b>Unit</b>       |
| <b>Rated heat output</b>   | Prated  | 4            | kW          | <b>Seasonal space heating energy efficiency</b>  | $\eta_S$          | 137,8        | %                 |
| <b>Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj</b>   |   |              |             | <b>Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj</b> |                   |              |                   |
| Tj = -7°C  | Pdh   | 3,8          | kW          | Tj = -7°C  | COPd              | 2,01         | -                 |
| Tj = +2°C  | Pdh   | 2,3          | kW          | Tj = +2°C  | COPd              | 3,64         | -                 |
| Tj = +7°C  | Pdh   | 2,2          | kW          | Tj = +7°C  | COPd              | 4,56         | -                 |
| Tj = +12°C   | Pdh   | 2,3          | kW          | Tj = +12°C   | COPd              | 5,24         | -                 |
| Tj = bivalent temperature  | Pdh   | 3,8          | kW          | Tj = bivalent temperature  | COPd              | 2,01         | -                 |
| Tj = operation limit temperature   | Pdh   | 2,9          | kW          | Tj = operation limit temperature   | COPd              | 2,04         | -                 |
| For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)   | Pdh   | -            | kW          | For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)   | COPd              | -            | -                 |
| Bivalent temperature   | T <sub>biv</sub>  | -7           | °C          | For air-to-water heat pumps: Operation limit temperature   | TOL               | -10          | °C                |
| Cycling interval capacity for heating  | Pcyc  | -            | kW          | Cycling interval efficiency  | COPcyc            | -            | -                 |
| Degradation co-efficient (**)  | Cdh   | 1,0          | -           | Heating water operating limit temperature  | WTOL              | 65           | °C                |
| <b>Power consumption in modes other than active mode</b>   |   |              |             | <b>Supplementary heater</b>  |                   |              |                   |
| Off mode   | P <sub>OFF</sub>  | 0,011        | kW          | Rated heat output  | P <sub>sup</sub>  | 1,1          | kW                |
| Thermostat-off mode  | P <sub>TO</sub>   | -            | kW          | Type of energy input   | electrical        |              |                   |
| Standby mode   | P <sub>SB</sub>   | 0,011        | kW          |  |                   |              |                   |
| Crankcase heater mode  | P <sub>CK</sub>   | -            | kW          |  |                   |              |                   |
| <b>Other items</b>   |   |              |             |  |                   |              |                   |
| Capacity control   | variable  |              |             | For air-to-water heat pumps: Rated air flow rate, outdoors   | -                 | 1.200        | m <sup>3</sup> /h |
| sound power level, indoors/outdoors  | L <sub>WA</sub>   | 43 / 41      | dB          | For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger                   | -                 | -            | m <sup>3</sup> /h |
| Emissions of nitrogen oxides   | NO <sub>x</sub>   | -            | mg/kWh      |  |                   |              |                   |
| <b>For heat pump combination heater:</b>   |   |              |             |  |                   |              |                   |
| Declared load profile  | -   |              |             | Water heating energy efficiency  | $\eta_{wh}$       | -            | %                 |
| Daily electricity consumption  | Q <sub>elec</sub>   | -            | kWh         | Daily fuel consumption   | Q <sub>fuel</sub> | -            | kWh               |
| <b>Contact details</b>   | ait deutschland GmbH, Industriestr. 3, 95359 Kasendorf, Germany |              |             |  |                   |              |                   |
| (*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). |   |              |             |  |                   |              |                   |
| (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.  |   |              |             |  |                   |              |                   |

| Model  |   |         |        | Paros 4-2  |                   |       |                   |
|--|---|---------|--------|--|-------------------|-------|-------------------|
| Air-to-water heat pump: (yes/no)   |   |         |        | yes  |                   |       |                   |
| Brine-to-water heat pump: (yes/no)   |   |         |        | no   |                   |       |                   |
| Water-to-water heat pump: (yes/no)   |   |         |        | no   |                   |       |                   |
| Low-temperature heat pump: (yes/no)  |   |         |        | no   |                   |       |                   |
| Equipped with supplementary heater: (yes/no)   |   |         |        | yes  |                   |       |                   |
| combination heater with: (yes/no)  |   |         |        | no   |                   |       |                   |
| application: (low/medium)  |   |         |        | low  |                   |       |                   |
| climate: (colder/average/warmer)   |   |         |        | average  |                   |       |                   |
| Item   | Symbol  | Value   | Unit   | Item   | Symbol            | Value | Unit              |
| Rated heat output  | Prated  | 5       | kW     | Seasonal space heating energy efficiency   | $\eta_S$          | 180,1 | %                 |
| <b>Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj</b>   |   |         |        | <b>Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj</b> |                   |       |                   |
| Tj = -7°C  | Pdh   | 4,1     | kW     | Tj = -7°C  | COPd              | 2,47  | -                 |
| Tj = +2°C  | Pdh   | 2,8     | kW     | Tj = +2°C  | COPd              | 4,80  | -                 |
| Tj = +7°C  | Pdh   | 2,4     | kW     | Tj = +7°C  | COPd              | 6,07  | -                 |
| Tj = +12°C   | Pdh   | 2,4     | kW     | Tj = +12°C   | COPd              | 6,79  | -                 |
| Tj = bivalent temperature  | Pdh   | 4,1     | kW     | Tj = bivalent temperature  | COPd              | 2,47  | -                 |
| Tj = operation limit temperature   | Pdh   | 4,1     | kW     | Tj = operation limit temperature   | COPd              | 2,27  | -                 |
| For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)   | Pdh   | -       | kW     | For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)   | COPd              | -     | -                 |
| Bivalent temperature   | T <sub>biv</sub>  | -7      | °C     | For air-to-water heat pumps: Operation limit temperature   | TOL               | -10   | °C                |
| Cycling interval capacity for heating  | Pcych   | -       | kW     | Cycling interval efficiency  | COPcyc            | -     | -                 |
| Degradation co-efficient (**)  | Cdh   | 1,0     | -      | Heating water operating limit temperature  | WTOL              | 65    | °C                |
| <b>Power consumption in modes other than active mode</b>   |   |         |        | <b>Supplementary heater</b>  |                   |       |                   |
| Off mode   | P <sub>OFF</sub>  | 0,011   | kW     | Rated heat output  | P <sub>sup</sub>  | 0,9   | kW                |
| Thermostat-off mode  | P <sub>TO</sub>   | -       | kW     | Type of energy input   | electrical        |       |                   |
| Standby mode   | P <sub>SB</sub>   | 0,011   | kW     |  |                   |       |                   |
| Crankcase heater mode  | P <sub>CK</sub>   | -       | kW     |  |                   |       |                   |
| <b>Other items</b>   |   |         |        |  |                   |       |                   |
| Capacity control   | variable  |         |        | For air-to-water heat pumps: Rated air flow rate, outdoors   | -                 | 1.200 | m <sup>3</sup> /h |
| sound power level, indoors/outdoors  | L <sub>WA</sub>   | 43 / 41 | dB     | For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger                   | -                 | -     | m <sup>3</sup> /h |
| Emissions of nitrogen oxides   | NO <sub>x</sub>   | -       | mg/kWh |  |                   |       |                   |
| <b>For heat pump combination heater:</b>   |   |         |        |  |                   |       |                   |
| Declared load profile  | -   |         |        | Water heating energy efficiency  | $\eta_{wh}$       | -     | %                 |
| Daily electricity consumption  | Q <sub>elec</sub>   | -       | kWh    | Daily fuel consumption   | Q <sub>fuel</sub> | -     | kWh               |
| <b>Contact details</b>   | ait deutschland GmbH, Industriestr. 3, 95359 Kasendorf, Germany |         |        |  |                   |       |                   |
| (*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). |   |         |        |  |                   |       |                   |
| (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.  |   |         |        |  |                   |       |                   |