

WZSV



Single-family
homes, Multi-
family homes



New build,
renovation and
replacements



Indoor installation



Heating and
domestic hot water
up to 65 °C



Passive cooling



Inverter-driven



Refrigerant
R407C
R410A (WZSV 42)

The WZSV series combines two key features: compactness and convenience

A flexible operating concept, space-saving installation and a wide product range for almost any application in a detached or semi-detached house are just some of the benefits, whether for new builds or renovation projects.

The WZSV series heat pumps offer advantages right from the start, during transport and installation. The module box with integrated refrigeration circuit can be easily removed for transport, and all façade components can also be dismantled. Installation of the heat centre with built-in storage tank and hydraulics is quick and easy, and with its very small footprint (< 0.5 m²), it fits into any corner.

The modular system provides double sound insulation: this is why the heat pumps operate about as quietly as a modern fridge. With the Luxtronik 2.1, operation is child's play thanks to a rotary and push button. All settings can be conveniently stored in the controller.

The benefits at a glance:

- + Heating, cooling and domestic hot water up to 65 °C
- + 178 l Domestic hot water tank already included
- + Extremely compact and space-saving
- + Inverter-driven – modulating heating and cooling mode
- + Convenient service via the front
- + Very low noise emissions
- + Passive cooling (natural cooling)
- + Easy to transport and assemble
- + Removable cool box for transport
- + Top quality "Made in Germany"

Device	Performance data				
	Heating capacity	COP	Cooling capacity/efficiency		Sound power level
	B0/W35 min./max.	B0/W35 partial load	B10/W18 partial load	B15/W25 partial load	indoor
	[kW]		[kW]/EER	[kW]/EER	[dB(A)]
WZSV 92H3M	1,77 / 8,65	4,76	-	-	44
WZSV 122H3M	2,48 / 13,56	4,87	-	-	44
WZSV 42K3M	1,02 / 3,90	4,31	10,50	-	42
WZSV 92K3M	1,77 / 8,65	4,76	-	7,80	44
WZSV 122K3M	2,48 / 13,56	4,87	-	12,30	44

All information on heat output and COP in accordance with EN 14 511. All information on sound power level in accordance with DIN EN 12102-1. *Housing dimensions only

WZSV



↗ Dimensions* w x h x d:
598 x 730 x 1850 mm

📦 Weight:

242 kg (WZSV 92H3)	238 kg (WZSV 42K3)
250 kg (WZSV 122H3)	248 kg (WZSV 92K3)
	258 kg (WZSV 122K3)

Energy efficiency labelling		
Combination heater	Water heating	in combination with controller
A+++ up to D at 55 °C	A+ up to F / A+++ up to G	A+++ up to G at 55 °C
A+++	A++	A+++
A+++	A+++	A+++
A+++	A++	A++
A+++	A+++	A+++
A+++	A+++	A+++